



## Quadruplex Oil Free Claw Medical Vacuum System - Stack Mount

### System Description:

The *Global Vac & Air* quadruplex oil-free dry claw medical vacuum system is built as three skids bolted together for ease of transport and installation. Two of the skids consist of two dry claw vacuum pumps mounted on a vertical frame. The 3<sup>rd</sup> skid is built with a vertical receiver and a mounted and wired NFPA99 compliant quadruplex PLC control panel. The system is completely tested before shipment and is built with single point connection for process inlet, and system power. The complete assembly is finished in GLOBALVAC white and supplied with inlet and discharge flex connectors and vibration pads. The system is piped, wired and factory tested prior to shipment.

### Oil-Free Dry Claw Vacuum Pump:

The vacuum pumps are direct driven by a continuous duty TEFC motor available in 208-230/460/3/60 electrical service. Additional electrical supply options available upon request. The contact free operating principle provides a nearly maintenance-free operation. The pump is oil-free in the pumping chamber and only requires oil change of gear oil. Each pump is air cooled and rated for continuous operation at its ultimate pressure without overheating. Each pump contains:

- Integrated and pump mounted check valves
- 5 micron inlet filter with polyester element
- Internal inlet screen
- Pump isolation valve
- Oil sight glass (gear oil)
- Oil drain valve (gear oil)
- Exhaust high temperature switch
- Inlet & outlet flex connector

### Vacuum Receiver:

The vertical vacuum receiver is ASME coded and rated for 200 PSI and full vacuum. The receiver is equipped with sight glass, drain valve, 3 valve bypass, and single point process inlet valve. The receiver is epoxy lined for corrosion resistance.

### Quadruplex NFPA99 PLC Control Panel:

The system is controlled by a UL labeled quadruplex NFPA99 compliant PLC control panel. The controller provides automatic alternation of the pumps or simultaneous operation if needed. Supplied with comprehensive software package which will display system and pump status and allow adjustment of system parameters. The control panel is built with:

- Finger safe power distribution block
- Dual 120V control transformer with CB protection for primary and secondary circuits
- Dual 120vac/24vdc power supply
- Transformer switching circuit to allow backup transformer to power circuit in event of primary transformer failure
- Transformer/Power Supply failure warning circuit, activates system general warning relay and PLC display warning indicator if either should fail
- 7" color OIT with integrated Hand/Off/Auto
- Door mounted system disconnect
- Door mounted Emergency Stop button
- Adjustable run-on timer (frequent start protection) integrated into OIT
- 4-20ma transmitter to control pumps
- Selectable, Auto Timed Alternation (default), Auto Alternation or Manual Alternation
- Hour meter integrated into OIT
- Reserve (Lag) Unit in use indicator with audible alarm
- Dry contacts for remote monitoring
- Maintenance screens with adjustable intervals for tracking maintenance items
- UL508A listed NEMA 12 enclosure
- Low vacuum alarm which may be enabled/disabled
- Door mounted Bypass circuit with selector switch
- Panel mounted vacuum gauge
- Ethernet bulkhead for temporary site connection



**Quadruplex Oil Free Claw  
Medical Vacuum System - Stack Mount**

<b>Model Number*</b>	<b>Pump motor rating (HP)**</b>	<b>Maximum Vacuum (in. HgV)</b>	<b>Nominal Capacity (ACFM/pump)**</b>	<b>System Capacity @ 19" Hg (SCFM/system)**</b>	<b>Receiver size (Gallons)</b>	<b>System BTU/hr**</b>	<b>System FLA @ 460 V / 3 / 60 Hz</b>
VC05Q-XXM-20V	5.4	28.1	103	113	200	35,045	24.6
VC06Q-XXM-20V	6.4	26.9	141	155	200	41,534	29.2
VC07Q-XXM-20V	7.5	26.9	171	188	200	48,673	33
VC07Q-XXM-24V	7.5	26.9	171	188	240	48,673	33
VC08Q-XXM-20V	8.7	25.5	212	233	200	56,461	38.3
VC08Q-XXM-24V	8.7	25.5	212	233	240	56,461	38.3
VC10Q-XXM-20V	10	24.0	250	275	200	64,898	42
VC10Q-XXM-24V	10	24.0	250	275	240	64,898	42
VC15Q-XXM-20V	15	24.0	353	388	200	97,346	63
VC15Q-XXM-24V	15	24.0	353	388	240	97,346	63

\*XX in the model number is a placeholder for system voltage. 43=460V/3/60Hz, 23=230V/3/60Hz, 53=575V/3/60Hz

\*\* All data shown assumes 60 Hz electrical supply and one pump sitting idle for redundancy