



## **Triplex Oil-Less Rotary Vane Medical Vacuum System – Stack Mount**

### **System Description:**

The *Global Vac & Air* Triplex Oil-Less Rotary Vane Medical Vacuum System is built as two skids bolted together for ease of transport and installation. One skid consists of three oil-less rotary vane vacuum pumps mounted in a vertical configuration. The second skid consists of a mounted and wired triplex NFPA99 compliant PLC control panel and a vertical receiver. The system is completely tested before shipment and is built with single point connection for process inlet, discharge, and system power. The complete assembly is finished in GLOBALVAC white and supplied with inlet and discharge flex connectors and vibration pads. The system is piped, wired and factory tested prior to shipment.

### **Oil-Less Rotary Vane Vacuum Pump:**

The vacuum pumps are directly driven by a continuous duty TEFC motor available in 208-230/460/3/60 electrical service. Additional electrical supply options available upon request. Each pump is air cooled and rated for continuous operation at its ultimate pressure without overheating. Each pump contains:

- Integrated and pump mounted check valves
- 5-micron inlet filter with polyester element
- Built in suction filter
- Pump isolation valve
- Self-lubricating graphite composite vanes
- Exhaust high temperature switch
- 100% dry operation
- Inlet & outlet flex connector

### **Vacuum Receiver:**

The vacuum receiver is ASME coded and rated for 200 PSI and full vacuum. The receiver is equipped with sight glass, 3 valve tank bypass, drain valve, and single point process inlet valve. The receiver is epoxy lined for corrosion resistance.

### **Triplex NFPA99 PLC Control Panel:**

The system is controlled by a UL labeled triplex NFPA99 compliant PLC control panel. The controller provides automatic alternation of the pumps or simultaneous operation if needed. Supplied with comprehensive software package which will display system and pump status and allow adjustment of system parameters.

The control panel is built with:

- Finger safe power distribution block
- Dual 120V control transformer with CB protection for primary and secondary circuits
- Dual 120vac/24vdc power supply
- Transformer switching circuit to allow backup transformer to power circuit in event of primary transformer failure
- Transformer/Power Supply failure warning circuit, activates system general warning relay and PLC display warning indicator if either should fail
- 7" color OIT with integrated Hand/Off/Auto
- Door mounted system disconnect
- Door mounted Emergency Stop button
- Adjustable run-on timer (frequent start protection) integrated into OIT
- 4-20ma transmitter to control pumps
- Selectable, Auto Timed Alternation (default), Auto Alternation or Manual Alternation
- Hour meter integrated into OIT
- Reserve (Lag) Unit in use indicator with audible alarm
- Dry contacts for remote monitoring
- Maintenance screens with adjustable intervals for tracking maintenance items
- UL508A listed NEMA 12 enclosure
- Low vacuum alarm which may be enabled/disabled
- Door mounted Bypass circuit with selector switch
- Panel mounted vacuum gauge
- Ethernet bulkhead for temporary site connection



**Triplex Oil-Less Rotary Vane  
Medical Vacuum System – Stack Mount**

<b>Model Number*</b>	<b>Pump motor rating (HP)**</b>	<b>Maximum Vacuum (in. HgV)</b>	<b>Nominal Capacity (ACFM/pump)**</b>	<b>System Capacity @ 19" Hg (SCFM/system)**</b>	<b>Receiver size (Gallons)</b>	<b>System BTU/hr**</b>	<b>System FLA @ 460 V / 3 / 60 Hz</b>
VV04T-XXM-12V	4.8	26.6	66	48	120	20,767	14.6
VV06T-XXM-12V-008	6.4	23.6	91	67	120	27,690	19.5
VV06T-XXM-20V	6.4	24	128	94	200	27,690	19.5
VV08T-XXM-20V	8.9	24	169	124	200	38,506	26.1

\*XX in the model number is a placeholder for system voltage. 43=460V/3/60Hz, 23=230V/3/60Hz, 53=575V/3/60Hz

\*\* All data shown assumes 60 Hz electrical supply and one pump sitting idle for redundancy