



## **Simplex Lubricated Rotary Vane Industrial Vacuum System-Horizontal Tank mount**

### **System Description:**

The *Global Vac & Air* Simplex Lubricated Rotary Vane Industrial Vacuum System is built as one lubricated rotary vane vacuum pump mounted and piped to a horizontal receiver with a mounted and wired simplex control panel. The system is completely tested before shipment and is built with single point connection for process inlet, pump discharge and system power. The complete assembly is finished in GLOBALVAC gray and supplied with inlet and discharge flex connectors and vibration pads. The system is piped, wired and factory tested prior to shipment.

### **Oil Flooded Rotary Vane Vacuum Pump:**

The vacuum pump is direct driven by a continuous duty TEFC motor available in 208-230/460/3/60 electrical service. Additional electrical supply options available upon request. Each pump is air cooled and rated for continuous operation at an ultimate pressure of 29.9" HgV without overheating. Each pump contains:

- Most efficient IE3 motor in the industry
- Integrated anti suck back valve
- High efficiency oil separator element
- Pump mounted check valve
- 5 micron inlet filter with polyester element
- Pump isolation valve
- Oil tank with dual stage oil separation
- Air cooled oil cooler
- Oil sight glass
- Oil drain valve
- Single shaft direct drive
- Exhaust flex connector
- Inlet flex connector

### **Vacuum Receiver:**

The horizontal vacuum receiver is ASME coded and rated for 200 PSI and full vacuum. The receiver is equipped with sight glass, drain valve, and single point process inlet valve. Multiple receiver size options available.

### **Simplex Control Panel:**

The system is controlled by a UL labeled simplex mounted and wired control panel.

The control panel is built with:

- Line Voltage Motor Starter with Overload Protection
- 120 Volt Control Transformer with protected Primary and Secondary Circuits
- High temperature switch
- Hand/Off/Auto Selector Switch
- Vacuum Gauge
- Panel Mounted Vacuum Switch
- Run Light
- Hour Meter
- NEMA 12 Enclosure
- UL Listed



**Simplex Lubricated Rotary Vane  
Industrial Vacuum System-Horizontal Tank mount**

<b>Model Number*</b>	<b>Pump motor rating (HP)**</b>	<b>Maximum Vacuum (in. HgV)</b>	<b>Nominal Capacity (ACFM/pump)**</b>	<b>System Capacity @ 19" Hg (SCFM/system)**</b>	<b>Receiver size (Gallons)</b>	<b>System BTU/hr**</b>	<b>System FLA @ 460 V / 3 / 60 Hz</b>
VR01A-XXD-06H	1.2	29.9	18	6	60	2,596	2.4
VR02A-XXD-06H-005	2.4	29.9	28	10	60	5,192	4.1
VR02A-XXD-06H-006	2.4	29.9	32	12	60	5,192	4.1
VR02A-XXD-06H-007	2.4	29.9	46	17	60	5,192	4.1
VR02A-XXD-06H	2.4	29.9	49	18	60	5,192	4.1
VR03A-XXD-08H	3.5	29.9	71	26	80	7,571	5.6
VR06A-XXD-12H	6.4	29.9	116	42	120	13,845	9.7
VR08A-XXD-12H	8.9	29.9	141	52	120	19,253	12.5
VR08A-XXD-20H	8.9	29.9	141	52	200	19,253	12.5
VR12A-XXD-12H	12.1	29.9	211	77	120	26,175	16.9
VR12A-XXD-20H	12.1	29.9	211	77	200	26,175	16.9

\*XX in the model number is a placeholder for system voltage. 43=460V/3/60Hz, 23=230V/3/60Hz, 53=575V/3/60Hz

\*\* All data shown assumes 60 Hz electrical supply